

CORE : 751U



CoreCasys 751U ต่อยอดมาจาก Core 750GL แต่เพิ่มฟังก์ชัน Wireless แบบ 802.11 b/g/n มี RAM 64MB สามารถทำ VPN แบบ Site-to-Site หรือการทำ HotSpot ภายในตัวอุปกรณ์ ด้วย CPU ขนาด 680MHz Ram 64MB จึงสามารถ Block P2P (Bittorrent), Bandwidth Management, และ Firewall พร้อม Switch 5 Port 10/100/1000 ด้วยระบบปฏิบัติการ ROS นั้นเป็นระบบกึ่งเปิดที่สามารถพัฒนาต่อยอดได้ในหลากหลายรูปแบบ บจก.เอ็นเจ เน็ตเวิร์ค ขายอุปกรณ์พร้อมการ Support และสามารถผลัดกันให้ท่านใช้งานได้จนจบ Solution

VPN	4 Tunnel
VPN Protocol	IPSec, PPTP (Lan-to-Lan)
	Block P2P (Bit Torrent, Bit Comet)
	Bandwidth Management (จำกัดความเร็วเครื่องลูกข่ายแต่ละ IP)
	3 Dynamic DNS update
Wireless	802.11 b/g/n

CPU	Atheros AR7242 400MHz network processor
Memory	64MB DDR SDRAM onboard memory
Boot loader	RouterBOOT
Data storage	64MB onboard NAND memory chip
Ethernet	Five 10/100/1000 Mbit/s Gigabit Ethernet ports with Auto-MDI/X, L2MTU frame size up to 4074
Extras	Reset switch
LEDs	5 Ethernet LEDs, power, user (configurable)
Power options	Passive 9-30V PoE, Power Jack 9-30V
Consumption	~6W
Dimensions	113x89x28mm. Weight without packaging and cables: 129g
Operating temperature	-30C to +70C
Operating system	MikroTik RouterOS v5, Level4 license
Package contains	RB750GL, 12V power adapter